

1.	GENERAL INFORMATION		
1.1	Date updated:	Oct 08, 2020	
1.2	Vessel's name (IMO number):	Histria Coral (9301299)	
1.3	Vessel's previous name(s) and date(s) of change:	Not Applicable	
1.4	Date delivered/Builder (where built):	Mar 30, 2006/CONSTANTA SHIPYARD	
1.5	Flag/Port of Registry:	Malta/Valletta	
1.6	Call sign/MMSI:	9HLB8/256105000	
1.7	Vessel's contact details (satcom/fax/email etc.):	Please contact operator	
1.8	Type of vessel (as described in Form A or Form B Q1.11 of the IOPPC):	Oil Tanker	
1.9	Type of hull:	Double Hull	
Ownership and Operation			
1.10	Registered owner - Full style:	MABLE MARINE CO. LTD 198, OLD BAKERY STREET, VALLETTA, MALTA Malta	
1.11	Technical operator - Full style:	Histria ShipManagement Srl Oborului Street 24,900162 Constanta Romania Romania Tel: +40 241 694894 Fax: +40 241 694746 Telex: Not Applicable Email: office@histria.ro ; operations@histria.ro Web: www.histria.ro	
1.12	Commercial operator - Full style:	Histria Shipmanagement SRL 24 Obrului Str., Constanta Romania Tel: 0040241694894 Fax: 0040241694746 Email: operations@histria.ro; office@histria.ro Web: www.histria.ro	
1.13	Disponent owner - Full style:	N/A	
Insurance			
1.14	P & I Club - Full Style:	UK CLUB	
1.15	P & I Club pollution liability coverage/expiration date:	1,000,000,000 US\$	Feb 20, 2021
1.16	Hull & Machinery insured by - Full Style: (Specify broker or leading underwriter)	London Market	
1.17	Hull & Machinery insured value/expiration date:		Jul 01, 2021
Classification			
1.18	Classification society:	DNV GL	
1.19	Class notation:	100 A5 Chemical tanker Type 3 oil tanker with double hull BWM ERS ESP NAV-O RSD MC AUT EP-D inert	
1.20	Is the vessel subject to any conditions of class, class extensions, outstanding memorandums or class recommendations? If yes, give details:	No	
1.21	If classification society changed, name of previous and date of change:	N/A, Not Applicable	
1.22	Does the vessel have ice class? If yes, state what level:	No, N/A	
1.23	Date/place of last dry-dock:	May 15, 2019/Constanta	
1.24	Date next dry dock due/next annual survey due:	Mar 29, 2021	Jun 29, 2021
1.25	Date of last special survey/next special survey due:	Apr 05, 2016	Mar 29, 2021
1.26	If ship has Condition Assessment Program (CAP), what is the latest overall rating:	No,	
Dimensions			

1.27	Length overall (LOA):	179.96 Metres		
1.28	Length between perpendiculars (LBP):	172.00 Metres		
1.29	Extreme breadth (Beam):	32.20 Metres		
1.30	Moulded depth:	16.50 Metres		
1.31	Keel to masthead (KTM)/ Keel to masthead (KTM) in collapsed condition, if applicable:	44.00 Metres	Not applicable	
1.32	Distance bridge front to center of manifold:	62.32 Metres		
1.33	Bow to center manifold (BCM)/Stern to center manifold (SCM):	89.94 Metres	90.02 Metres	
1.34	Parallel body distances	Lightship	Normal Ballast	Summer Dwt
	Forward to mid-point manifold:	27.74 Metres	40.60 Metres	43.10 Metres
	Aft to mid-point manifold:	33.75 Metres	49.40 Metres	62.70 Metres
	Parallel body length:	61.486 Metres	90 Metres	105.80 Metres

Tonnages

1.35	Net Tonnage:	11,366.00		
1.36	Gross Tonnage/Reduced Gross Tonnage (if applicable):	25,804.00	20,233	
1.37	Suez Canal Tonnage - Gross (SCGT)/Net (SCNT):	26,357.40	25,314.09	
1.38	Panama Canal Net Tonnage (PCNT):	21,516.00		

Loadline Information

1.39	Loadline	Freeboard	Draft	Deadweight	Displacement
	Summer:	5.592 Metres	10.922 Metres	39,999 Metric Tonnes	49,610 Metric Tonnes
	Winter:	5.82 Metres	10.694 Metres	38,759 Metric Tonnes	48,406 Metric Tonnes
	Tropical:	5.364 Metres	11.15 Metres	41,170 Metric Tonnes	50,817 Metric Tonnes
	Lightship:	13.914 Metres	2.60 Metres	-	9,692.20 Metric Tonnes
	Normal Ballast Condition:	9.614 Metres	6.90 Metres	19,739.71 Metric Tonnes	29,387.31 Metric Tonnes
	Segregated Ballast Condition:	9.60 Metres	6.90 Metres	19,739.71 Metric Tonnes	29,387.31 Metric Tonnes
1.40	FWA/TPC at summer draft:			236 Millimetres	52.50 Metric Tonnes
1.41	Does vessel have multiple SDWT? If yes, please provide all assigned loadlines:	Yes 40426 37767 39999 29999 34999			
1.42	Constant (excluding fresh water):	100 Metric Tonnes			
1.43	What is the company guidelines for Under Keel Clearance (UKC) for this vessel?	Please contact operator			
1.44	What is the max height of mast above waterline (air draft)			Full Mast	Collapsed Mast
	Summer deadweight:			33.078 Metres	0 Metres
	Normal ballast:			36.80 Metres	0 Metres
	Lightship:			41.40 Metres	0 Metres

2.	CERTIFICATES	Issued	Last Annual	Last Intermediate	Expires
2.1	Safety Equipment Certificate (SEC):	Apr 05, 2016	May 13, 2019	May 13, 2019	Mar 29, 2021
2.2	Safety Radio Certificate (SRC):	Jun 11, 2018	May 13, 2019	May 13, 2019	Mar 29, 2021
2.3	Safety Construction Certificate (SCC):	Jun 11, 2018	May 13, 2019	May 13, 2019	Mar 29, 2021
2.4	International Loadline Certificate (ILC):	Apr 05, 2016	Feb 22, 2019		Mar 29, 2021
2.5	International Oil Pollution Prevention Certificate (IOPPC):	Jun 11, 2018	May 13, 2019	May 13, 2019	Mar 29, 2021

2.6	International Ship Security Certificate (ISSC):	Apr 06, 2016	Not Applicable	Apr 05, 2019	Apr 06, 2021
2.7	Maritime Labour Certificate (MLC):	Mar 27, 2018	N/A	Not Applicable	Jun 20, 2023
2.8	ISM Safety Management Certificate (SMC):	Apr 06, 2016	Not Applicable	Apr 05, 2019	Apr 06, 2021
2.9	Document of Compliance (DOC):	Dec 08, 2017	Nov 20, 2019		Oct 23, 2022
2.10	USCG Certificate of Compliance(USCGCOC):				
2.11	Civil Liability Convention (CLC) 1992 Certificate:	Feb 20, 2020	N/A	N/A	Feb 20, 2021
2.12	Civil Liability for Bunker Oil Pollution Damage Convention (CLBC) Certificate:	Feb 20, 2019	N/A	N/A	Feb 20, 2021
2.13	Liability for the Removal of Wrecks Certificate (WRC):	Feb 20, 2020	N/A	N/A	Feb 20, 2021
2.14	U.S. Certificate of Financial Responsibility (COFR):	May 16, 2015	N/A	N/A	May 16, 2021
2.15	Certificate of Class (COC):	Jun 11, 2018	Jun 29, 2020	May 13, 2019	Mar 29, 2021
2.16	International Sewage Pollution Prevention Certificate (ISPPC):	Jun 11, 2018	N/A	N/A	Mar 29, 2021
2.17	Certificate of Fitness (COF):	Jun 01, 2018	May 13, 2019	May 13, 2019	Mar 29, 2021
2.18	International Energy Efficiency Certificate (IEEC):	Jun 12, 2014	N/A	N/A	N/A
2.19	International Air Pollution Prevention Certificate (IAPPC):	Jun 11, 2018	May 13, 2019	May 13, 2019	Mar 29, 2021

Documentation					
2.20	Owner warrant that vessel is member of ITOPF and will remain so for the entire duration of this voyage/contract:				Yes
2.21	Does vessel have in place a Drug and Alcohol Policy complying with OCIMF guidelines for Control of Drugs and Alcohol Onboard Ship?				Yes
2.22	Is the ITF Special Agreement on board (if applicable)?				Yes
2.23	ITF Blue Card expiry date (if applicable):				May 30, 2021

3.	CREW				
3.1	Nationality of Master:				Romanian
3.2	Number and nationality of Officers:	7			Romanian
3.3	Number and nationality of Crew:	12			ROMANIAN
3.4	What is the common working language onboard:				Romanian and English
3.5	Do officers speak and understand English?				Yes
3.6	If Officers/ratings employed by a manning agency - Full style:	Officers: N/A			Ratings: N/A

4.	FOR USA CALLS				
4.1	Has the vessel Operator submitted a Vessel Spill Response Plan to the US Coast Guard which has been approved by official USCG letter?				Yes
4.2	Qualified individual (QI) - Full style:	Gallagher Marine Systems Inc 200 Century Parkway, Suite D Alt. 24 Hour Phone: +1 215 492 5473 Mt. Laurel, NJ 08054 Tel: +1 703 683 4700 / +1 Fax: +1 856 642 3945 Telex: N/A Email: info@chgms.com			
4.3	Oil Spill Response Organization (OSRO) - Full style:	NATIONAL RESPONSE CORPORATION 3500 SUNRISE HIGHWAY SUITE T103, GREAT RIVER NY 11739 USA Tel: +16312249141 Fax: +16312249086 Telex: 4961 7380 NRC UI Email: iocdo@nrcc.com Web: N/A			
4.4	Salvage and Marine Firefighting Services (SMFF) - Full Style:	RESOLVE MARINE GROUP 1510 SE 17th Street Suite 400			

		Fort Lauderdale ,FL.33316 Tel: +1 954 764 8700 Web: www.resolveopa.com
--	--	--

5.	SAFETY/HELICOPTER	
5.1	Is the vessel operated under a Quality Management System? If Yes, what type of system? (ISO9001 or IMO Resolution A.741(18) as amended):	Yes ISO 9002
5.2	Can the ship comply with the ICS Helicopter Guidelines?	Yes
5.2.1	If Yes, state whether winching or landing area provided:	Winching
5.2.2	If Yes, what is the diameter of the circle provided:	5.20 Metres

6.	COATING/ANODES				
6.1	Tank Coating	Coated	Type	To What Extent	Anodes
	Cargo tanks:	Yes	EPOXY / SIGMAGUARD EHB	Whole Tank	No
	Ballast tanks:	Yes	MULTIMASTIC EPOXY 440	Whole Tank	No
	Slop tanks:	Yes	EPOXY / SIGMAGUARD EHB	Whole Tank	No

7.	BALLAST				
7.1	Pumps	No.	Type	Capacity	At What Head (sg=1.0)
	Ballast Pumps:	2	Framo Centrifugal	800 Cu. Metres/Hour	25 Metres
	Ballast Eductors:	1	N/A	85 Cu. Metres/Hour	3 Metres

8.	CARGO				
Double Hull Vessels					
8.1	Is vessel fitted with centerline bulkhead in all cargo tanks? If Yes, solid or perforated:	Yes, Solid			
Cargo Tank Capacities					
8.2	Number of cargo tanks and total cubic capacity (max% per company policy: 98%, 97%, 96% or 95%) excluding slops tanks:	10	46,822 Cu. Metres		
8.2.1	Capacity (max% per company policy: 98%, 97%, 96% or 95%) of each natural segregation with double valve (specify tanks):	Seg#1: 7106.6 m3 - 1W (98%) Seg#2: 9866.1 m3 - 2W (98%) Seg#3: 10110.8 m3 - 3W (98%) Seg#4: 10109.8 m3 - 4W (98%) Seg#5: 9627.3 m3 - 5W (98%)			
8.2.2	IMO class (Oil/Chemical Ship Type 1, 2 or 3):	3			
8.3	Number of slop tanks and total cubic capacity (max% per company policy: 98%, 97%, 96% or 95%):	2	981 Cu. Metres		
8.3.1	Specify segregations which slops tanks belong to and their capacity with double valve:	Independents: Cargo Tk 6P = 395 cbm Cargo Tk 6S = 586 cbm with double valve segregation			
8.3.2	Residual/retention oil tank(s) capacity (98%), if applicable:	189 Cu. Metres			
SBT Vessels					
8.3.3	What is total SBT capacity and percentage of SDWT vessel can maintain?	18,653.50 Cu. Metres	46.10 %		
8.3.4	Does vessel meet the requirements of MARPOL Annex I Reg 18.2:	Yes			
Cargo Handling and Pumping Systems					
8.4	How many grades/products can vessel load/discharge with double valve segregation:	5			
8.4.1	State type of cargo containment (integral, independent, gravity or pressure tanks):	1P (Independent Pressure)			
8.5	Are there any cargo tank filling restrictions?	No			

	If yes, specify number of slack tanks, max s.g., ullage restrictions etc.:		
8.6	Max loading rate for homogenous cargo	With VECS	Without VECS
	Loaded per manifold connection:	2,500 Cu. Metres/Hour (2500 cbm/hr if 12" VECS connection or lower as per Terminal restrictions)	2,500 Cu. Metres/Hour (with min 6 cargo tanks open simultaneously)
	Loaded simultaneously through all manifolds:	3,750 Cu. Metres/Hour (3750 cbm/hr if 12" VECS connection or lower as per Terminal restrictions)	3,750.00 Cu. Metres/Hour
Cargo Control Room			
8.7	Is ship fitted with a Cargo Control Room (CCR)?	Yes	
8.8	Can tank innage/ullage be read from the CCR?	Yes	
Gauging and Sampling			
8.9	Is gauging system certified and calibrated? If no, specify which ones are not calibrated:	Yes, One of the middle ones is calibrated	
	What type of gauging system as per IBC 13.1 is fitted (Open/Restricted/Closed)?	Closed	
	What type of fixed closed tank gauging system is fitted:	Radar	
	Is a tank overflow control system fitted? If yes, then state if system includes automatic closing of valves?	Yes,	
	Are high level alarms fitted to the cargo tanks? If Yes, indicate whether to all tanks or partial:	Yes, All	
8.9.1	Can cargo be transferred under closed loading conditions in accordance with ISGOTT 11.1.6.6?	Yes	
8.9.2	Are cargo tanks fitted with multipoint gauging? If yes, specify type and locations:	Yes, MB 2", 1 fore, two middle, 1 aft	
8.10	Number of portable gauging units (example- MMC) on board:	4	
Vapor Emission Control System (VECS)			
8.11	Is a vapour return system (VRS) fitted?	Yes	
8.12	Number/size of VECS manifolds (per side):	2	254 Millimetres
8.13	Number/size/type of VECS reducers:	4 x 254/304.8 mm (10/12")	
Venting			
8.14	State what type of venting system is fitted:	Pres-Vac	
Cargo Manifolds and Reducers			
8.15	Total number/size of cargo manifold connections on each side:	5/304.80 Millimetres	
8.15.1	Does the vessel have a Common Line Manifold connection? If yes, describe:	Yes. All manifolds are connected with a cross over line	
8.16	What type of valves are fitted at manifold:	Butterfly / Manually	
8.17	What is the material/rating of the manifold:	STAINLESS STEEL/ANSI B16.5	
8.17.1	Does vessel comply with the latest edition of the OCIMF 'Recommendations for Oil Tanker Manifolds and Associated Equipment'?	Yes	
8.18	Distance between cargo manifold centers:	2,000.00 Millimetres	
8.19	Distance ships rail to manifold:	4,600.00 Millimetres	
8.20	Distance manifold to ships side:	4,600.00 Millimetres	
8.21	Top of rail to center of manifold:	800.00 Millimetres	
8.22	Distance main deck to center of manifold:	1,900.00 Millimetres	
8.23	Spill tank grating to center of manifold:	900.00 Millimetres	
8.24	Manifold height above the waterline in normal ballast/at SDWT condition:	11.50 Metres	7.492 Metres
8.25	Number/size/type of reducers:	10 x 406.4/304.8mm (16/12") 4 x 304.8/254mm (12/10") 4 x 304.8/203.2mm (12/8") 4 x 304.8/304.8mm (12/12") ANSI	

8.26	Is vessel fitted with a stern manifold? If yes, state size:			Yes, 304.80 Millimetres	
Heating					
8.27	Cargo/slop tanks fitted with a cargo heating system?	Type	Coiled	Material	
	Cargo Tanks:	DECK HEATERS / HEATING COILS (slops)	No (heating coils only in slop tks; cargo tanks -heat exchangers on deck)	SS	
	Slop Tanks:	HEATING COILS / stem	Yes	SS	
8.27.1	Is a Thermal Oil Heating system fitted? If yes, identify tanks?			No,	
8.28	Maximum temperature cargo can be loaded/maintained:			70.0 °C / 158.0 °F	65 °C / 149 °F
8.28.1	Minimum temperature cargo can be loaded/maintained:			15 deg C above pour point	
Inert Gas and Crude Oil Washing					
8.29	Is an Inert Gas System (IGS) fitted/operational?			Yes/Yes	
8.29.1	Is a Crude Oil Washing (COW) installation fitted/operational?			Yes/Yes	
8.30	Is IGS supplied by flue gas, inert gas (IG) generator and/or nitrogen:			IG Generator	
8.30.1	If nitrogen generator, specify the applicable flow rate for each of the designed purity modes:				
Cargo Pumps					
8.31	How many cargo pumps can be run simultaneously at full capacity:			6	
8.32	Pumps	No.	Type	Capacity	At What Head (sg=1.0)
	Cargo Pumps:	10 2 1 1	Framo Centrifugal Framo Centrifugal Framo Centrifugal Framo Centrifugal	500 M3/HR 200 M3/HR 150 M3/HR 80 M3/HR	125 Meters 125 Meters 125 Meters 70 Meters
	Cargo Eductors:		N/A		
	Stripping:	1	Framo Reciprocating	30 Cu. Metres/Hour	100 Metres
8.33	Is at least one emergency portable cargo pump provided?			Yes	
Tank Cleaning Systems					
8.34	Is tank cleaning equipment fixed in cargo tanks?			Yes	
8.35	Is portable tank cleaning equipment provided?			Yes	
8.36	Tank washing pump capacity:			150.00 Cu. Metres/Hour	
8.37	Is a washing water heater fitted? If yes is it operational and state max washing water temperature:			Yes, Yes 85.00 Degrees Celsius	
8.38	What is the maximum number of machines that can be operated at their designed max pressure?			4	
Other Deck Equipment					
8.39	Is vessel fitted with a remote cargo tank temperature monitoring system. If yes, is it operational?			Yes, Yes	
8.40	Is vessel fitted with a remote cargo tank pressure monitoring system. If yes, is it operational?			Yes, Yes	
8.41	Is vessel fitted with a cargo tank drier. If yes is it operational and state capacity:			No, N/A	
8.42	Is vessel fitted with a cargo cooling system. If yes is it operational and state tanks applicable:			No, N/A	
8.43	Is steam available on deck?			No	

9.	MOORING					
9.1	Wires (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:			Not Applicable		
	Main deck fwd:			Not Applicable		
	Main deck aft:			Not Applicable		
	Poop deck:			Not Applicable		

9.2	Wire tails	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	8	60 Millimetres	40% Polyester + 60% Nikasteel	11.00 Metres	75 Metric Tonnes
	Main deck fwd:	2	60 Millimetres	40% Polyester + 60% Nikasteel	11.00 Metres	75 Metric Tonnes
	Main deck aft:	2	60 Millimetres	40% Polyester + 60% Nikasteel	11.00 Metres	75 Metric Tonnes
	Poop deck:	6	60 Millimetres	40% Polyester + 60% Nikasteel	11.00 Metres	75 Metric Tonnes
9.3	Ropes (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	4	26.00 Millimetres	HMPE	220.00 Metres	54 Metric Tonnes
	Main deck fwd:	2	26.00 Millimetres	HMPE	220.00 Metres	54 Metric Tonnes
	Main deck aft:	2	26.00 Millimetres	HMPE	220.00 Metres	54 Metric Tonnes
	Poop deck:	4	26.00 Millimetres	HMPE	220.00 Metres	54 Metric Tonnes
9.4	Other lines	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	4	26.00 Millimetres	HMPE	220.00 Metres	54 Metric Tonnes
	Main deck fwd:			Not Applicable		
	Main deck aft:			Not Applicable		
	Poop deck:	2	26.00 Millimetres	HMPE	220.00 Metres	54 Metric Tonnes
9.5	Winches	No.	No. Drums	Motive Power	Brake Capacity	Type of Brake
	Forecastle:	2	Double Split Drums	Hydraulic	55.00 Metric Tonnes	
	Main deck fwd:	1	Double Split Drums	Hydraulic	55.00 Metric Tonnes	
	Main deck aft:	1	Double Split Drums	Hydraulic	55.00 Metric Tonnes	
	Poop deck:	2	Double Split Drums	Hydraulic	55.00 Metric Tonnes	
9.6	Bitts, closed chocks/fairleads		No. Bitts	SWL Bitts	No. Closed Chocks	SWL Closed Chocks
	Forecastle:		8	64 Metric Tonnes	11	56 Metric Tonnes
	Main deck fwd:		2	64 Metric Tonnes	6	56 Metric Tonnes
	Main deck aft:		2	64 Metric Tonnes	6	56 Metric Tonnes
	Poop deck:		10	64 Metric Tonnes	13	56 Metric Tonnes
Anchors/Emergency Towing System						
9.7	Number of shackles on port/starboard cable:				12/12	
9.8	Type/SWL of Emergency Towing system forward:				ROLLS-ROYCE	200 Metric Tonnes
9.9	Type/SWL of Emergency Towing system aft:				COSALT 1000KN	100 Metric Tonnes
9.10.1	What is size of closed chock and/or fairleads of enclosed type on stern				600 x 450	
Escort Tug						
9.10.2	What is SWL of closed chock and/or fairleads of enclosed type on stern:				100.00 Metric Tonnes	
9.11	What is SWL of bollard on poop deck suitable for escort tug:				100.00 Metric Tonnes	
Lifting Equipment/Gangway						
9.12	Derrick/Crane description (Number, SWL and location):				Cranes: 1 x 10.00 Tonnes center	
9.13	Accommodation ladder direction:				Aft	
	Does vessel have a portable gangway? If yes, state length:				Yes, 13.00 Metres	
Single Point Mooring (SPM) Equipment						
9.14	Does the vessel meet the recommendations in the latest edition of OCIMF 'Recommendations for Equipment Employed in the Bow Mooring of Conventional Tankers at Single Point Moorings (SPM)':?				Yes	
9.15	If fitted, how many chain stoppers:				1	
9.16	State type/SWL of chain stopper(s):				TONGUE TYPE	200.00 Metric

			Tonnes
9.17	What is the maximum size chain diameter the bow stopper(s) can handle:		76.00 Millimetres
9.18	Distance between the bow fairlead and chain stopper/bracket:		3,040.00 Metres
9.19	Is bow chock and/or fairlead of enclosed type of OCIMF recommended size (600mm x 450mm)? If not, give details of size:	Yes Not Applicable	

10.	PROPULSION		
10.1	Speed	Maximum	Economical
	Ballast speed:	15 Knots (WSNP)	12.50 Knots (WSNP)
	Laden speed:	14 Knots (WSNP)	12 Knots (WSNP)
10.2	What type of fuel is used for main propulsion/generating plant:	VLSFO / MGO	VLSFO / MGO
10.3	Type/Capacity of bunker tanks:	Fuel Oil: 1,079.80 Cu. Metres Diesel Oil: Gas Oil: 424 Cu. Metres	
10.4	Is vessel fitted with fixed or controllable pitch propeller(s):	Fixed	
10.5	Engines	No	Capacity
	Main engine:	1	8,230 Kilowatt
	Aux engine:	3	880 Kilowatt
	Power packs:	4	3,000 Cu. Metres
	Boilers:	2	16.00 Metric Tonnes/Hour
			6S50 MCC L23/30H MAN 2 x Cummings Engine Company+ 2 x Siemens Com SAACKE MARINE SYSTEM (steam boiler + composite)
Bow/Stern Thruster			
10.6	What is brake horse power of bow thruster (if fitted):	Yes, 1,155.00 bhp	
10.7	What is brake horse power of stern thruster (if fitted):	No,	
Emissions			
10.8	Main engine IMO NOx emission standard:	Tier I	
10.9	Energy Efficiency Design Index (EEDI) rating number:	n/a	

11.	SHIP TO SHIP TRANSFER		
11.1	Does vessel comply with recommendations contained in OCIMF/ICS Ship To Ship Transfer Guide (Petroleum, Chemicals or Liquefied Gas, as applicable)?	Yes	
11.2	What is maximum outreach of cranes/derricks outboard of the ship's side:	4.75 Metres	
11.3	Date/place of last STS operation:	Please contact operator	

12.	RECENT OPERATIONAL HISTORY		
12.1	Last three cargoes/charterers/voyages (Last/2nd Last/3rd Last):	Please contact operator	
12.2	Has vessel been involved in a pollution, grounding, serious casualty, unscheduled repair or collision incident during the past 12 months? If yes, provide details:	Pollution: No, N/A Grounding: No, N/A Casualty: No, Repair: No, Collision: No, N/A	
12.3	Date and place of last Port State Control inspection:	Mar 22, 2020 / Odessa	
12.4	Any outstanding deficiencies as reported by any Port State Control? If yes, provide details:	No NIL	
12.5	Recent Oil company inspections/screenings (To the best of owners knowledge and without guarantee of acceptance for future business)*: * "Approvals" are not given by Oil Majors and ships are accepted for the voyage on a case by case basis.	AS PER RECAP	

12.6	Date/Place of last SIRE inspection:	Please contact operator
12.6.1	Date/Place of last CDI inspection:	/ N/A
12.7	Additional information relating to features of the ship or operational characteristics:	

Revised 2018 ([INTERTANKO/Q88.com](http://www.intertanko.com))

Form completed on <http://www.q88.com/integration.aspx> Please email support@q88.com an updated copy if this is not the latest version.

To the best of owners knowledge all information is true and given without any guarantee.